



LURI SERIES

240W - FLOOD MOUNT
Product Spec Sheet



COMMERCIAL-GRADE

LED Flood Light

Product Overview

Elevate your spaces with Luri Series by Hetria Lighting. These cutting-edge LED lights feature integrated drivers, high lumen efficiency, built-in surge protection, UL listing for safety, and a 3-year warranty.

Experience innovation that's smaller, brighter, and environmentally friendly. Illuminate responsibly with Hetria Lighting!

Built to withstand the test of time, our units boast an impressive IP65 waterproof rating and are capable of enduring any harsh weather condition ensuring optimal outdoor performance. Illuminate your world with confidence and reliability.

Product Warranty



3-Year
Limited Warranty



150,000 Hrs

Applications






Factories, Libraries, Parks, Residentials, Supermarkets, Railway Stations, Advertising lighting, etc

Main Features

- **Crystal-Clear White Light:** Drawing just 240W of input power, it delivers an impressive 34,800 lumens. Dimming not available.
- **Elegant & Aesthetic Fixture and Housing:** Design to complement the light, crafted from aluminum with rich, enduring black powder coat for timeless beauty.
- **Flood Mount:** Allows for adjustable positioning on surfaces like walls, poles or ceilings, enabling precise lighting direction.
- **Elegance Meets Performance:** Its stylish design is matched by its impressive functionality so you can install with absolute confidence thanks to its reassuring 3-Year limited warranty.
- **UL Listed:** When you choose UL Certified products you are selecting Superior Quality, Enhance Safety & Unmatched Reliability.
- **Integrated Driver (Driver on Board):** Compact, Sleek & Lightweight! The integrated driver reduces the size, streamlines the design, and lightens the fixture making it more space-efficient for installation with a pleasing appearance.
- **Advanced driver is rated for 120-277VAC exclusively.**
- **Suitable for use in -22° F to 113° F**
- **Eco-friendly:** Printed on recycled material to reduce waste.



Model Specifications

Features	Description
Input Wattage	 240 Watts. Replace 500-600W MH HPS or 1000W Incandescent
Kelvin Color	 5000K Bright White Light
LED Chip	 Bridgelux SMD2835
Lumen Performance	 145Lm/Watt. 240W=34800 Lumens
Surge Protection	 2kV Built-in for Extended Lifespan

Key Specifications

- Dimming: NA
- Efficacy: <145lm/W
- Input Voltage & Frequency: 120-277VAC 50/60Hz
- IP: IP65 Waterproof Rating
- Power Factor (PF): > .94
- Total Harmonic Distortion (THD): <30%
- Color Rendering Index (CRI): >80
- Housing & Lens: Die-cast aluminum/ Clear Tempered Glass
- Operating Temperature: -22°F - 113°F

Certifications



Model Specifications

Model	WATT(W)	Lumens (lm)	Efficacy (lm/W)	Mount Type	Kelvin Color (K)	Voltage (V)	CRI
Luri Series	30W	3,450lm	115lm/W	KM/YM	5000K	120VAC	>80
	50W	5,750lm	115lm/W	KM/YM			
	80W	9,200lm	115lm/W	KM/YM			
Luri Series w/PC	150W	17,250	115/lm/W	AM/FM	5000K	120-277VAC	>80
	240W	34,800	145/lm/W	AM/FM			

LURI SERIES

LED FLOOD LIGHT



5 YEAR
WARRANTY



5000K CCT
BRIGHT WHITE



120°
BEAM ANGLE



BRIDGELUX
2835 LEDs




CRI 80+



2KV
SURGE PROTECTION
BUILT-IN



Mounting Options


Knuckle Mount (KM):



Yoke Mount (YM):



Flood Mount (FM):



Slip Fit Mount (AM)



Photometric Results – 240W Luri Series Led Flood Light

Luminaire Property



Luminaire Manufacturer:
Voltage: 120.3 V
Power: 258.10 W

Current: 2.156 A
Power Factor: 0.995

Photometric Results

IES Classification: Type I
Total Rated Lamp Lumens: 37417.8 lm
Efficiency: 100%
Upward Ratio: 1%
Central Intensity: 29786.46 cd
Pos of Max. Intensity: H180 V12

Longitudinal Classification: Very Short
Measurement Flux: 37417.8 lm
Downward Ratio: 99%
Luminaire Efficacy Rating (LER): 145.02
Max. Intensity: 31420.7 cd



Sizing & Measurement

Model Series	Height (in)	Length (in)	Width (in)	Net Weight (lbs)	Measurements Diagram
Luri Series 30W KM	7.40	5.98	1.02	1.23	
Luri Series 30W YM	6.25	5.98	1.02	1.23	
Luri Series 50W KM	8.14	7.16	1.18	1.47	
Luri Series 50W YM	7.04	7.16	1.18	1.47	

Sizing & Measurement

Model Series	Height (in)	Length (in)	Width (in)	Net Weight (lbs)	Measurements Diagram
Luri Series 80W KM	9.17	8.34	1.37	1.91	
Luri Series 80W YM	8.03	8.34	1.37	1.91	
Luri Series 150W AM	15.55	11.81	2.44	6.82	
Luri Series 150W / 240W FM	11.77	12.44	2.44	6.09	