

500W STADIUMPRO V | LED SPORT LIGHT



RuggedGrade

PRODUCT DESCRIPTION

The StadiumPro Series reaches new heights with the Series V! It boasts enhanced efficiency, delivering an impressive 160 Lumens per watt. Equipped with top-of-the-line uPowerTek Driver, it offers versatile mounting options and advanced optics. The Stadium Pro V is UL Listed and DLC Premium 6.0 Certification this upcoming fall, solidifying its status as the Pinnacle of sports lighting!







PART #: RGL-STADIUMPRO-5-500W

DLC#: S-HY6CZQ

PRODUCT FEATURES & COMMON USE APPLICATIONS

- ✓ UL cUL
- ✓ Input voltage 277-480Vac
- ✓ No UV or IR in the beam
- ✓ Easy to install and operate
- ✓ Energy saving, long lifespan
- ✓ Instant start, NO flickering, NO humming
- ✓ Green and eco-friendly without mercury
- ✓ Output constant current lever can be adjusted through output cable with 0-10V.
- ✓ Stadium Fields
- ✓ Gymnasium
- ✓ Square plaza
- ✓ Shipyard, Airport, wharf
- ✓ High mast and Contour lighting, etc.

PRODUCT DIMENSIONS



LEGENDARY USA SUPPORT




US based
phone and online
customer support

DLC
CERTIFIED

5 YEARS
WARRANTY

UL
LISTED



Rugged Grade Lighting
Industrial Grade Solutions



888-953-2476
sales@ruggedgrade.com



PRODUCT TECHNICAL SPECIFICATIONS

OPTICAL	Input Power (Tolerance: $\pm 10\%$)	500W (Wattage adjustable 25%-100%)		
	Color Temperature	4000K	5000K	5700K
	Lumen (Tolerance: -10%)	80,500 LM	81,000 LM	81,500 LM
	Efficacy (Tolerance: -3%)	161 LM/W	162 LM/W	163 LM/W
	CRI	>70		
	Color Consistency	< 6 Steps (or < 6 SDCM)		
	BUG	B5-U0-G5		
	Distribution Pattern	NEMA:4 (Optional:NEMA:4/NEMA:5)		
	Beam Angle (50%) (Tolerance: $\pm 15\%$)	$20^{\circ} \pm 3^{\circ}$ (Optional: $(30^{\circ} \pm 5^{\circ}) / (40^{\circ} \pm 5^{\circ})$)		
ELECTRICAL	Input Voltage and Frequency	277-480VAC, 50/60Hz		
	PF (Tolerance: -3%)	≥ 0.9		
	THD (Tolerance: +5%)	$\leq 20\%$		
	Flicker Percent	<5%		
	Driver Brand	uPowerTek		
	Driver Model	BLD-500-C320-ENU		
	Driver Surge protection	L/N-PE: 10kV, L-N:6kV		
	Dimming	0-10V dimming standard		
	Optional Accessory	Sensor Receptacle+Photosensor /Sensor Receptacle+Short Cap, 10KV and Optional of 20KV for Surge-protective Device, Zhaga		
MATERIALS	LED Brand	LUMILEDS		
	LED Type	SMD 2835		
	LED QTY	600 PCS		
	Housing	Die-cast aluminum		
	Housing Color	Black, White, Bronze, or Customized		
	EPA	1.7 ft ²		
	Waterproof Rating	WET (IP65)		
	Operating Temperature	-40°C TO 45°C		
OTHERS	Storage Temperature	-40°C TO 80°C		
	Operating Humidity	20% - 90% RH		
	Storage Humidity	10% - 95% RH		
	Warranty	5 years warranty with 24/7 operating hours Luminaire lifetime at 25°C.		




500W STADIUMPRO V | LED SPORT LIGHT





PRODUCT IMAGES & ACTUAL INSTALLATIONS




Actual install - ECMX Motorsports Park MT



Actual Install - 144qty - 1200 watt Stadium Pro Lights
Santa Fe Springs Event Center, Los Angeles CA



Actual Install - StadiumPro LED Sports Lights
Keystone Fieldhouse, PA



Actual Install - White Field Newark OH - 1200w Stadium Pro Lights

Rugged Grade Lighting
Industrial Grade Solutions



888-953-2476
sales@ruggedgrade.com



PHOTOMETRICS

STREETLIGHT PHOTOMETRIC TEST REPORT

Test:U:118.61V I:4.2199A P:499.06W PF:0.9971 Freq:60.01Hz

Lamp Flux:81358.5x1 lm



NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:

DATA OF LAMP

PHOTOMETRIC DATA

Eff: 163.02 lm/W

MODEL		Imax (cd)	278141	η street_up(%)	0.2
NOMINAL POWER (W)	500	LOR (%)	100.0	η street_down(%)	57.0
RATED VOLTAGE (V)	120	TOTAL FLUX (lm)	81359	η house_up(%)	0.2
NOMINAL FLUX (lm)	81358.5	MAXIMUM @ (C, γ)	90, 3.0	η house_down(%)	42.6
LAMPS INSIDE	1	η up (%)	0.4	76 FLASHAREA (m2)	0.05000
TEST VOLTAGE (V)	120	η down (%)	99.6	SLI	22.886

INTENSITY DISTRIBUTION DIAGRAM
IN C PLANS

DLC PRODUCT SPECS



DLC QPL / Products / Product Details

Model Number

RGL-StadiumPro-5-500WBS4H1-acdWf57

Manufacturer

RuggedGrade

Brand

RUGGEDGRADE



● SSL V6.0 Premium Product ID: S-HY6CZQ

Product Overview 19 fields	
CATEGORY ⓘ Outdoor Luminaires	GENERAL APPLICATION ⓘ Very High Output
PRIMARY USE ⓘ Sports Lighting	CLASSIFICATION ⓘ Premium
TECHNICAL REQUIREMENTS VERSION ⓘ 6.0	DLC FAMILY CODE ⓘ KKGJQS
BRAND ⓘ RUGGEDGRADE	
PARENT No	LISTING STATUS Listed
DATE QUALIFIED 2026-08-20	
REPORTED INPUT WATTAGE ⓘ 497.8 W	REPORTED LIGHT OUTPUT ⓘ 83,642 lm
REPORTED CCT ⓘ 5700 K	REPORTED CRI ⓘ 71
REPORTED R9 ⓘ -29	REPORTED IES RF 71
REPORTED IES RG 96	REPORTED IES RCS,H1 -17
INPUT POWER TYPE ⓘ AC	




500W STADIUMPRO V | LED SPORT LIGHT



PRODUCT PACKAGING

Bracket Type	Carton Size	Qty / Carton	Net Weight / Carton	Gross Weight / Carton
FM	600*480*370mm	1 PC	14.7KG	17KG
	[23.62*18.90*14.57inch]		[32.41LBS]	[37.48LBS]
AM	600*480*370mm	1 PC	14.7KG	17KG
	[23.62*18.90*14.57inch]		[32.41LBS]	[37.48LBS]



PRODUCT WARNINGS

- Please turn off power before install or change assembly parts.
- The input voltage and lamps should be matched, after connecting the power line.
- Please make sure the wiring section is insulated.
- Professionals must install and disassemble the lamps.
- Surge is the number 1 cause of LED light failure. Outdoor lights must have surge at fixture, pole, and breaker.
- Surge is the number 1 cause of LED light failure. Indoor lights must have surge at fixture and breaker.

PRODUCT TROUBLESHOOTING

Issue	Check points
Light Flickers	Check all wiring for disconnections, shorts and burnt wiring and connections. Confirm steady input voltage to the light fixture, fluctuating input voltage will harm the LED driver and can lead to premature failure. Lights with photocells can have photocell tag from ambient light or light reflecting at the sensor. Simply cover the photocell completely and see if flickering continues while the photocell is covered. Call Tech Support for help if none of the above solves the issue.
Light does not work at all.	Check all wiring for disconnections, shorts and burnt wiring and connections. Confirm steady input voltage to the light fixture, fluctuating input voltage will harm the LED driver and can lead to premature failure. If input voltage is not in the voltage range of the fixture, you will need to find the source of your input voltage issue. Call Tech Support for help if none of the above solves the issue.

For more technical information, install questions, troubleshooting help or warranty claims, we have a dedicated US Tech and Customer Support Team to help solve any issues you have and can be reached by email or phone. If you need help with any of our products, we are here for you so that you are never in the dark!

BETTER LIGHTS. BETTER SUPPORT.

